

SAFETY DATA SHEET

1. Identification

Product identifier	SEALANT 2XH-SF	
Other means of identification		
Product code	800-0037	
Recommended use	Industrial Leak Sealant.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Company name	Team Industrial Services, Inc.	
Address	200 Hermann Drive, Alvin, Texas 77511	
Telephone	Not available.	
E-mail	Not available.	
Emergency phone number	CHEMTREC - 24 HOURS:	800-424-9300 (USA)
	International:	+1 703-527-3887 (Collect)

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 4
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
	Environmental hazards	Hazardous to the aquatic environment, acute hazard
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Combustible liquid. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be allowed out of the workplace. Avoid breathing mist or vapor. Wash thoroughly after handling. Avoid release to the environment.
Response	If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
Storage	Store in a well-ventilated place. Keep cool.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Aluminum hydroxide	21645-51-2	25-50
Aluminum oxide	1344-28-1	25-50
Phenol, polymer with formaldehyde	9003-35-4	10-25
Ethanol	64-17-5	5-10
Graphite	7782-42-5	5-10
Carbon fiber	7440-44-0	<5
m-Cresol	108-39-4	<5
p-Cresol	106-44-5	<5
2,6-Xylenol	576-26-1	<1
Hexamethylenetetramine	100-97-0	<1
Phenol	108-95-2	<1
o-Ethylphenol	90-00-6	<1

Composition comments All concentrations are in percent by weight.

4. First-aid measures

Inhalation

Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.

When cured: Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Skin contact

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops and persists.

Eye contact

Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion

Rinse mouth thoroughly with water and give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Obtain medical attention and take along these instructions.

Most important symptoms/effects, acute and delayed

Symptoms include redness, itching and pain. May cause permanent damage if eye is not immediately irrigated. Sensitization. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Treat symptomatically. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

No restrictions known.

Specific hazards arising from the chemical

Solvent vapors may form explosive mixtures with air. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Fire fighting equipment/instructions

Ventilate closed spaces before entering them. Containers should be cooled with water to prevent vapor pressure build up. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Evacuate area and fight fire from a safe distance. Stop leak if you can do so without risk. Move containers from fire area if you can do it without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

The product is combustible.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Ensure adequate ventilation. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not get in eyes. Avoid inhalation of vapors or mists. Avoid contact with skin. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Clean contaminated surface thoroughly. Sweep up or vacuum up spillage and collect in suitable container for disposal. Never return spills in original containers for re-use. This material and its container must be disposed of as hazardous waste. Collect and dispose of spillage as indicated in Section 13 of the SDS.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water. Environmental manager must be informed of all major spillages.

7. Handling and storage**Precautions for safe handling**

Use only with adequate ventilation. Persons susceptible for allergic reactions should not handle this product. Do not get in eyes. Avoid inhalation of vapors or mists. Avoid contact with skin. The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. Do not smoke and do not spray near a naked flame or other sources of ignition. Vapors are heavier than air and may travel along the floor and in the bottom of containers. Take precautionary measures against static discharges. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

Follow rules for combustible liquids. Keep away from heat, spark, open flames and other sources of ignition. Keep away from sources of ignition - No smoking. Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials.

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Aluminum oxide (CAS 1344-28-1)	PEL	5 mg/m ³	Respirable fraction.
Ethanol (CAS 64-17-5)	PEL	15 mg/m ³	Total dust.
		1900 mg/m ³	
Graphite (CAS 7782-42-5)	PEL	1000 ppm	Respirable fraction.
		5 mg/m ³	
m-Cresol (CAS 108-39-4)	PEL	15 mg/m ³	Total dust.
		22 mg/m ³	
p-Cresol (CAS 106-44-5)	PEL	5 ppm	
		22 mg/m ³	
		5 ppm	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Carbon fiber (CAS 7440-44-0)	TWA	15 mppcf
Graphite (CAS 7782-42-5)	TWA	15 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum hydroxide (CAS 21645-51-2)	TWA	1 mg/m ³	Respirable fraction.
Aluminum oxide (CAS 1344-28-1)	TWA	1 mg/m ³	Respirable fraction.
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
m-Cresol (CAS 108-39-4)	TWA	20 mg/m3	Inhalable fraction and vapor.
p-Cresol (CAS 106-44-5)	TWA	20 mg/m3	Inhalable fraction and vapor.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Carbon fiber (CAS 7440-44-0)	TWA	2.5 mg/m3	Respirable.
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3 1000 ppm	
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
m-Cresol (CAS 108-39-4)	TWA	10 mg/m3 2.3 ppm	
p-Cresol (CAS 106-44-5)	TWA	10 mg/m3 2.3 ppm	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines No exposure standards allocated.

US - California OELs: Skin designation

m-Cresol (CAS 108-39-4) Can be absorbed through the skin.
p-Cresol (CAS 106-44-5) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

m-Cresol (CAS 108-39-4) Skin designation applies.
p-Cresol (CAS 106-44-5) Skin designation applies.

US - Tennessee OELs: Skin designation

m-Cresol (CAS 108-39-4) Can be absorbed through the skin.
p-Cresol (CAS 106-44-5) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

m-Cresol (CAS 108-39-4) Can be absorbed through the skin.
p-Cresol (CAS 106-44-5) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

m-Cresol (CAS 108-39-4) Can be absorbed through the skin.
p-Cresol (CAS 106-44-5) Can be absorbed through the skin.

Appropriate engineering controls Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors. An eye wash and safety shower must be available in the immediate work area.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear protective gloves. Butyl rubber gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Skin protection

Other Wear appropriate clothing to prevent possibility of skin contact.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Black pliable semi-solid with phenolic odor.

Physical state Solid.

Form Pliable semi-solid.

Color	Black.
Odor	Phenolic.
Odor threshold	0.003 - 5 ppm (m-Cresol)
pH	Not available.
Melting point/freezing point	Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	160.0 °F (71.1 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Slightly.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Flammability	Combustible liquid.
Flash point class	Combustible IIIA

10. Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Flames and sparks. Avoid static discharge and uncontrolled exposure to high temperatures. Contact with incompatible materials.
Incompatible materials	Strong oxidizers, strong acids, and strong bases. Strong reducing agents.
Hazardous decomposition products	At elevated temperatures: Carbon oxides. Formaldehyde. Nitrogen oxides (NOx).

11. Toxicological information

Information on likely routes of exposure

Inhalation	In high concentrations, vapors may be irritating to the respiratory system. May cause lung edema. When cured: Vapors, spray or mists may be very irritating or corrosive to the respiratory system.
Skin contact	Causes skin irritation. May cause an allergic skin reaction. May be harmful in contact with skin. The product contains components which may penetrate skin.
Eye contact	Causes severe eye damage.
Ingestion	May cause central nervous system depression. May cause blood damage. May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms include redness, itching and pain. May cause permanent damage if eye is not immediately irrigated. Sensitization. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity May be harmful if swallowed. May be harmful in contact with skin.

Components	Species	Test Results
-------------------	----------------	---------------------

Aluminum hydroxide (CAS 21645-51-2)

Acute*Oral*

LD50

Rat

> 5000 mg/kg

Carbon fiber (CAS 7440-44-0)

Acute*Oral*

LD50

Rat

> 10000 mg/kg

Ethanol (CAS 64-17-5)

Acute*Inhalation*

LC50

Rat

30000 mg/m³

m-Cresol (CAS 108-39-4)

Acute*Dermal*

LD50

Rabbit

620 mg/kg

Oral

LD50

Rat

242 mg/kg

p-Cresol (CAS 106-44-5)

Acute*Dermal*

LD50

Rabbit

300 mg/kg

Oral

LD50

Rat

207 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization**Respiratory sensitization**

No data available.

Skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Not classified. Contains a component that is suspected of causing genetic defects.

Carcinogenicity

No data available.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity

No data available.

Specific target organ toxicity - single exposure

No data available.

Specific target organ toxicity - repeated exposure

No data available.

Aspiration hazard

Based on available data, the classification criteria are not met.

Chronic effects Danger of serious damage to health by prolonged exposure. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. When cured: Phenolic resin releases formaldehyde and formaldehyde has carcinogenic potential and is a known skin and respiratory sensitizer.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results	
m-Cresol (CAS 108-39-4)			
Aquatic			
Crustacea	EC50	Scud (Gammarus fasciatus)	7 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	8.9 mg/l, 96 hours
p-Cresol (CAS 106-44-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7.7 mg/l, 48 hours
Fish	LC50	Fish (Lepidocephalichthyes guntea)	6.15 - 7.96 mg/l, 96 hours

Persistence and degradability No data available.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Ethanol (CAS 64-17-5)	-0.31
m-Cresol (CAS 108-39-4)	1.96
p-Cresol (CAS 106-44-5)	1.94

Mobility in soil Expected to be slightly to moderately mobile in soil.

Mobility in general The product is slightly soluble in water.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Dispose of this material and its container to hazardous or special waste collection point. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Hazardous waste code D026: Waste Cresol
When cured: Not regulated.

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	NA1993
UN proper shipping name	Combustible liquid, n.o.s. (Ethanol)
Transport hazard class(es)	
Class	- Combustible Liquid
Subsidiary risk	-
Packing group	III
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. This material is not regulated under 49 CFR if in a container of 119 gallon capacity or less.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethanol (CAS 64-17-5)	LISTED
m-Cresol (CAS 108-39-4)	LISTED
p-Cresol (CAS 106-44-5)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminum oxide	1344-28-1	25-50
m-Cresol	108-39-4	<5
p-Cresol	106-44-5	<5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

m-Cresol (CAS 108-39-4)
p-Cresol (CAS 106-44-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Aluminum oxide (CAS 1344-28-1)
Carbon fiber (CAS 7440-44-0)
Ethanol (CAS 64-17-5)
Graphite (CAS 7782-42-5)
m-Cresol (CAS 108-39-4)
p-Cresol (CAS 106-44-5)

US. New Jersey Worker and Community Right-to-Know Act

Aluminum oxide (CAS 1344-28-1)
Carbon fiber (CAS 7440-44-0)
Ethanol (CAS 64-17-5)
Graphite (CAS 7782-42-5)
m-Cresol (CAS 108-39-4)
p-Cresol (CAS 106-44-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum oxide (CAS 1344-28-1)
Carbon fiber (CAS 7440-44-0)
Ethanol (CAS 64-17-5)
Graphite (CAS 7782-42-5)
m-Cresol (CAS 108-39-4)
p-Cresol (CAS 106-44-5)

US. Rhode Island RTK

Aluminum oxide (CAS 1344-28-1)
m-Cresol (CAS 108-39-4)

p-Cresol (CAS 106-44-5)

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 15-April-2015

Revision date 08-February-2016

Version # 02

Further information HMIS® is a registered trade and service mark of the NPCA.
J - Goggles, Gloves, Apron, Dust, Vapor Respirator

HMIS® ratings Health: 3
Flammability: 2
Physical hazard: 0
Personal protection: J

References ACGIH
EPA: Acquire database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
ESIS (European chemical Substances Information System)
IARC: International Agency for Research on Cancer.

Disclaimer Team Industrial Services, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

This SDS contains revisions in the following section(s): 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16.