

SAFETY DATA SHEET

1. Identification

| | | |
|---|---------------------------------------|---------------------------|
| Product identifier | SEALANT 2XH | |
| Other means of identification | | |
| Product code | 800-0025 | |
| Recommended use | Industrial Leak Sealant. | |
| Recommended restrictions | None known. | |
| Manufacturer/Importer/Supplier/Distributor information | | |
| Company name | Team Industrial Services, Inc. | |
| Address | 200 Hermann Drive, Alvin, Texas 77511 | |
| Telephone | Not available. | |
| E-mail | Not available. | |
| | | |
| Emergency phone number | CHEMTREC - 24 HOURS: | 800-424-9300 (USA) |
| | International: | +1 703-527-3887 (Collect) |

2. Hazard(s) identification

| | | |
|------------------------------|--|------------|
| Physical hazards | Flammable liquids | Category 4 |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 1 |
| | Sensitization, skin | Category 1 |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 3 |
| | Hazardous to the aquatic environment, long-term hazard | Category 3 |
| OSHA defined hazards | Not classified. | |

Label elements



| | |
|--|---|
| Signal word | Danger |
| Hazard statement | Combustible liquid. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. |
| Precautionary statement | |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be allowed out of the workplace. Avoid breathing mist or vapor. Wash thoroughly after handling. Avoid release to the environment. |
| Response | If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction. |
| Storage | Store in a well-ventilated place. Keep cool. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | CAS number | % |
|-----------------------------|-------------|-------|
| Aluminum hydroxide | 21645-51-2 | 25-50 |
| Phenol-formaldehyde polymer | 9003-35-4 | 10-25 |
| Quartz | 14808-60-7 | 10-25 |
| Ethanol | 64-17-5 | 5-10 |
| Graphite | 7782-42-5 | 5-10 |
| Aluminosilicate | 142844-00-6 | 1-5 |
| Carbon fiber | 7440-44-0 | 1-5 |
| m-Cresol | 108-39-4 | 1-5 |
| p-Cresol | 106-44-5 | 1-5 |
| 2,6-Xylenol | 576-26-1 | <1 |
| Hexamethylenetetramine | 100-97-0 | <1 |
| O-Ethylphenol | 90-00-6 | <1 |
| Phenol | 108-95-2 | <1 |

Composition comments All concentrations are in percent by weight.

4. First-aid measures

Inhalation

Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.
When cured: Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Skin contact

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion

Rinse mouth thoroughly with water and give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Obtain medical attention and take along these instructions.

Most important symptoms/effects, acute and delayed

Symptoms include redness, itching and pain. May cause permanent damage if eye is not immediately irrigated. Sensitization. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Treat symptomatically. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

No restrictions known.

Specific hazards arising from the chemical

Solvent vapors may form explosive mixtures with air. During fire, gases hazardous to health may be formed.

| | |
|--|--|
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. |
| Fire fighting equipment/instructions | Ventilate closed spaces before entering them. Containers should be cooled with water to prevent vapor pressure build up. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Evacuate area and fight fire from a safe distance. Stop leak if you can do so without risk. Move containers from fire area if you can do it without risk. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | The product is combustible. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Ensure adequate ventilation. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not get in eyes. Avoid inhalation of vapors or mists. Avoid contact with skin. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Eliminate all ignition sources. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Clean contaminated surface thoroughly. Sweep up or vacuum up spillage and collect in suitable container for disposal. Never return spills in original containers for re-use. This material and its container must be disposed of as hazardous waste. Collect and dispose of spillage as indicated in Section 13 of the SDS. |
| Environmental precautions | Prevent further leakage or spillage if safe to do so. Do not contaminate water. Environmental manager must be informed of all major spillages. |

7. Handling and storage

| | |
|---|--|
| Precautions for safe handling | Use only with adequate ventilation. Persons susceptible for allergic reactions should not handle this product. Do not get in eyes. Avoid inhalation of vapors or mists. Avoid contact with skin. The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. Do not smoke and do not spray near a naked flame or other sources of ignition. Vapors are heavier than air and may travel along the floor and in the bottom of containers. Take precautionary measures against static discharges. Use personal protective equipment as required. |
| Conditions for safe storage, including any incompatibilities | Follow rules for combustible liquids. Keep away from heat, spark, open flames and other sources of ignition. Keep away from sources of ignition - No smoking. Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--------------------------|------|---|-------------------------------------|
| Ethanol (CAS 64-17-5) | PEL | 1900 mg/m ³ 1000 ppm | |
| Graphite (CAS 7782-42-5) | PEL | 5 mg/m ³ 15 mg/m ³ | Respirable fraction. Total dust. |
| m-Cresol (CAS 108-39-4) | PEL | 22 mg/m ³ 5 ppm | |
| p-Cresol (CAS 106-44-5) | PEL | 22 mg/m ³ 5 ppm | |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|------------------------------|------|---|---|
| Carbon fiber (CAS 7440-44-0) | TWA | 15 mppcf | |
| Graphite (CAS 7782-42-5) | TWA | 15 mppcf | |
| Quartz (CAS 14808-60-7) | TWA | 0.3 mg/m ³ 0.1 mg/m ³ 2.4 mppcf | Total dust. Respirable. Respirable. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|-------------------------------------|------|---------------------|----------------------|
| Aluminum hydroxide (CAS 21645-51-2) | TWA | 1 mg/m ³ | Respirable fraction. |
| Ethanol (CAS 64-17-5) | STEL | 1000 ppm | |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|--------------------------|------|-------------------------|-------------------------------|
| Graphite (CAS 7782-42-5) | TWA | 2 mg/m ³ | Respirable fraction. |
| m-Cresol (CAS 108-39-4) | TWA | 20 mg/m ³ | Inhalable fraction and vapor. |
| p-Cresol (CAS 106-44-5) | TWA | 20 mg/m ³ | Inhalable fraction and vapor. |
| Quartz (CAS 14808-60-7) | TWA | 0.025 mg/m ³ | Respirable fraction. |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|-----------------------------------|------|------------------------------------|--------------------|
| Aluminosilicate (CAS 142844-00-6) | TWA | 3 fibers/cm ³ | Fiber. |
| | | 3 fibers/cm ³ | Dust. |
| | | 5 mg/m ³ | Fiber, total |
| | | 5 mg/m ³ | fibers, total dust |
| Carbon fiber (CAS 7440-44-0) | TWA | 2.5 mg/m ³ | Respirable. |
| Ethanol (CAS 64-17-5) | TWA | 1900 mg/m ³ 1000 ppm | |
| Graphite (CAS 7782-42-5) | TWA | 2.5 mg/m ³ | Respirable. |
| | | 10 mg/m ³ | |
| m-Cresol (CAS 108-39-4) | TWA | 2.3 ppm | |
| | | 10 mg/m ³ | |
| p-Cresol (CAS 106-44-5) | TWA | 2.3 ppm | |
| | | 10 mg/m ³ | |
| Quartz (CAS 14808-60-7) | TWA | 0.05 mg/m ³ | Respirable dust. |

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

m-Cresol (CAS 108-39-4)

Can be absorbed through the skin.

p-Cresol (CAS 106-44-5)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

m-Cresol (CAS 108-39-4)

Skin designation applies.

p-Cresol (CAS 106-44-5)

Skin designation applies.

US - Tennessee OELs: Skin designation

m-Cresol (CAS 108-39-4)

Can be absorbed through the skin.

p-Cresol (CAS 106-44-5)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

m-Cresol (CAS 108-39-4)

Can be absorbed through the skin.

p-Cresol (CAS 106-44-5)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

m-Cresol (CAS 108-39-4)

Can be absorbed through the skin.

p-Cresol (CAS 106-44-5)

Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors. An eye wash and safety shower must be available in the immediate work area.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection

Wear protective gloves. Butyl rubber gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Skin protection

Other

Wear appropriate clothing to prevent possibility of skin contact.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

| | |
|---|--|
| Appearance | Black pliable semi-solid with phenolic odor. |
| Physical state | Solid. |
| Form | Pliable semi-solid. |
| Color | Black. |
| Odor | Phenolic. |
| Odor threshold | 0.003 - 5 ppm (m-Cresol) |
| pH | Not available. |
| Melting point/freezing point | Not applicable. |
| Initial boiling point and boiling range | Not applicable. |
| Flash point | 165.0 °F (73.9 °C) Tag Closed Cup |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | Not available. |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Slightly. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | > 1200 °F (> 648.89 °C) when cured |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Flammability | Combustible liquid. |
| Flash point class | Combustible IIIA |

10. Stability and reactivity

| | |
|---|--|
| Reactivity | The product is non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Flames and sparks. Avoid static discharge and uncontrolled exposure to high temperatures. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizers, strong acids, and strong bases. Strong reducing agents. |
| Hazardous decomposition products | At elevated temperatures: Carbon oxides. Formaldehyde. Nitrogen oxides (NOx). |

11. Toxicological information**Information on likely routes of exposure**

| | |
|-------------------|---|
| Inhalation | In high concentrations, vapors may be irritating to the respiratory system. May cause lung edema. When cured: Vapors, spray or mists may be very irritating or corrosive to the respiratory system. |
|-------------------|---|

Skin contact Causes skin irritation. May cause an allergic skin reaction. May be harmful in contact with skin. The product contains components which may penetrate skin.

Eye contact Causes severe eye damage.

Ingestion May cause central nervous system depression. May cause blood damage. May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Symptoms include redness, itching and pain. May cause permanent damage if eye is not immediately irrigated. Sensitization. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity May be harmful if swallowed. May be harmful in contact with skin.

| Components | Species | Test Results |
|------------|---------|--------------|
|------------|---------|--------------|

Aluminum hydroxide (CAS 21645-51-2)

Acute

Oral

| | | |
|------|-----|--------------|
| LD50 | Rat | > 5000 mg/kg |
|------|-----|--------------|

Carbon fiber (CAS 7440-44-0)

Acute

Oral

| | | |
|------|-----|---------------|
| LD50 | Rat | > 10000 mg/kg |
|------|-----|---------------|

Ethanol (CAS 64-17-5)

Acute

Inhalation

| | | |
|------|-------|-------------------------------|
| LC50 | Mouse | 39 g/m ³ , 4 Hours |
|------|-------|-------------------------------|

Oral

| | | |
|------|-----|--------------------|
| LD50 | Rat | 7000 - 11000 mg/kg |
|------|-----|--------------------|

m-Cresol (CAS 108-39-4)

Acute

Dermal

| | | |
|------|--------|-----------|
| LD50 | Rabbit | 620 mg/kg |
|------|--------|-----------|

Oral

| | | |
|------|-----|-----------|
| LD50 | Rat | 242 mg/kg |
|------|-----|-----------|

p-Cresol (CAS 106-44-5)

Acute

Dermal

| | | |
|------|--------|-----------|
| LD50 | Rabbit | 300 mg/kg |
|------|--------|-----------|

Oral

| | | |
|------|-----|-----------|
| LD50 | Rat | 207 mg/kg |
|------|-----|-----------|

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Not classified. Contains a component that is suspected of causing genetic defects.

Carcinogenicity Inhalation of quartz dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|-----------------------------------|-------------------------------------|
| Aluminosilicate (CAS 142844-00-6) | 2B Possibly carcinogenic to humans. |
|-----------------------------------|-------------------------------------|

| | |
|-------------------------|---------------------------|
| Quartz (CAS 14808-60-7) | 1 Carcinogenic to humans. |
|-------------------------|---------------------------|

NTP Report on Carcinogens

| | |
|-------------------------|-------------------------------|
| Quartz (CAS 14808-60-7) | Known To Be Human Carcinogen. |
|-------------------------|-------------------------------|

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

| | |
|---|--|
| Reproductive toxicity | No data available. |
| Specific target organ toxicity - single exposure | No data available. |
| Specific target organ toxicity - repeated exposure | No data available. |
| Aspiration hazard | Based on available data, the classification criteria are not met. |
| Chronic effects | Danger of serious damage to health by prolonged exposure. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. When cured: Phenolic resin releases formaldehyde and formaldehyde has carcinogenic potential and is a known skin and respiratory sensitizer. |
| Further information | The intended use of this product does not include grinding. |

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

| Components | | Species | Test Results |
|-------------------------|------|--|----------------------------|
| Ethanol (CAS 64-17-5) | | | |
| Aquatic | | | |
| Fish | LC50 | Pimephales promelas | 13480 mg/l, 96 hours |
| m-Cresol (CAS 108-39-4) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Scud (Gammarus fasciatus) | 7 mg/l, 48 hours |
| Fish | LC50 | Rainbow trout, donaldson trout (Oncorhynchus mykiss) | 8.9 mg/l, 96 hours |
| p-Cresol (CAS 106-44-5) | | | |
| Aquatic | | | |
| Crustacea | EC50 | Water flea (Daphnia magna) | 7.7 mg/l, 48 hours |
| Fish | LC50 | Fish (Lepidocephalichthyes guntea) | 6.15 - 7.96 mg/l, 96 hours |

Persistence and degradability No data available.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

| | |
|-------------------------|------|
| m-Cresol (CAS 108-39-4) | 1.96 |
| p-Cresol (CAS 106-44-5) | 1.94 |

Mobility in soil Expected to be slightly to moderately mobile in soil.

Mobility in general The product is slightly soluble in water.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Dispose of this material and its container to hazardous or special waste collection point. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Hazardous waste code D026: Waste Cresol
When cured: Not regulated.

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

| | |
|--------------------------------|--------------------------------------|
| UN number | NA1993 |
| UN proper shipping name | Combustible liquid, n.o.s. (Ethanol) |

Transport hazard class(es)**Class** - Combustible Liquid**Subsidiary risk** -**Packing group** III**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.
This material is not regulated under 49 CFR if in a container of 119 gallon capacity or less.**IATA**

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.**Annex II of MARPOL 73/78 and
the IBC Code****15. Regulatory information****US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Aluminosilicate (CAS 142844-00-6) 0.1 % One-Time Export Notification only.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

m-Cresol (CAS 108-39-4) LISTED

p-Cresol (CAS 106-44-5) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories** Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous
chemical** Yes**SARA 313 (TRI reporting)**

| Chemical name | CAS number | % by wt. |
|---------------|------------|----------|
| m-Cresol | 108-39-4 | 1-5 |
| p-Cresol | 106-44-5 | 1-5 |

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

m-Cresol (CAS 108-39-4)

p-Cresol (CAS 106-44-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act
(SDWA)** Not regulated.**US state regulations****US. Massachusetts RTK - Substance List**

Aluminosilicate (CAS 142844-00-6)

Carbon fiber (CAS 7440-44-0)

Ethanol (CAS 64-17-5)

Graphite (CAS 7782-42-5)

m-Cresol (CAS 108-39-4)

p-Cresol (CAS 106-44-5)

Quartz (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Aluminosilicate (CAS 142844-00-6)

Carbon fiber (CAS 7440-44-0)
Ethanol (CAS 64-17-5)
Graphite (CAS 7782-42-5)
m-Cresol (CAS 108-39-4)
p-Cresol (CAS 106-44-5)
Quartz (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminosilicate (CAS 142844-00-6)
Carbon fiber (CAS 7440-44-0)
Ethanol (CAS 64-17-5)
Graphite (CAS 7782-42-5)
m-Cresol (CAS 108-39-4)
p-Cresol (CAS 106-44-5)
Quartz (CAS 14808-60-7)

US. Rhode Island RTK

m-Cresol (CAS 108-39-4)
p-Cresol (CAS 106-44-5)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Quartz (CAS 14808-60-7)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | No |

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|---|---|
| Issue date | 28-October-2015 |
| Revision date | 08-February-2016 |
| Version # | 02 |
| Further information | HMIS® is a registered trade and service mark of the NPCA. J - Goggles, Gloves, Apron, Dust, Vapor Respirator |
| HMIS® ratings | Health: 3 Flammability: 2 Physical hazard: 0 Personal protection: J |
| References | ACGIH EPA: Acquire database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents HSDB® - Hazardous Substances Data Bank IARC Monographs. Overall Evaluation of Carcinogenicity National Toxicology Program (NTP) Report on Carcinogens ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices ESIS (European chemical Substances Information System) IARC: International Agency for Research on Cancer. |
| Disclaimer | Team Industrial Services, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. |
| This SDS contains revisions in the following section(s): | 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 14, 15, 16. |