

TEAM[®] Industrial Services

SAFETY DATA SHEET

1. Identification

Product identifier S-200 PRP SEALANT

Other means of identification

Product code 900-0024

Recommended use Industrial Leak Sealant.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Team Industrial Services, Inc.
Address 200 Hermann Drive, Alvin, Texas 77511
Telephone Not available.
E-mail Not available.

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300 (USA)
International: +1 703-527-3887 (Collect)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Health hazards Skin corrosion/irritation Category 1B
Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Germ cell mutagenicity Category 2
Specific target organ toxicity, repeated exposure Category 2 (kidney, liver)

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of causing genetic defects. May cause damage to organs (kidney, liver) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe vapor/spray. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response In case of fire: Use appropriate media for extinction. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Aluminum hydroxide	21645-51-2	25-50
Phenol, polymer with formaldehyde	9003-35-4	10-25
Quartz	14808-60-7	10-25
Ethanol	64-17-5	5-10
Graphite	7782-42-5	5-10
Carbon fiber	7440-44-0	1-5
Refractories, Fibers, Aluminosilicate	142844-00-6	1-5
m-Cresol	108-39-4	1-5
p-Cresol	106-44-5	1-5
2,6-Xylenol	576-26-1	<1
Hexamethylenetetramine	100-97-0	<1
O-Ethylphenol	90-00-6	<1

Composition comments

All concentrations are in percent by weight.

Refractories, Fibers, Aluminosilicate Note R: The classification as a carcinogen does not apply according to Directive 67/548/EEC as it can be shown that fibers have a length weighted geometric mean diameter less two standard geometric errors greater than 6 micrometers.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Get medical attention immediately.

Skin contact

Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.

Eye contact

Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion

Rinse mouth thoroughly with water and give large amounts of milk or water, if person is conscious. Never give anything by mouth to a victim who is unconscious or is having convulsions. Only induce vomiting at the instruction of medical personnel. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Get medical attention immediately.

Most important symptoms/effects, acute and delayed

Unconsciousness. Coughing. Shortness of breath. Discomfort in the chest. Irritation of nose and throat. Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness and tearing. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure.

Indication of immediate medical attention and special treatment needed

Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure.

General information

Chemical burns must be treated by a physician.

5. Fire-fighting measures

Suitable extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

No restrictions known.

Specific hazards arising from the chemical

Solvent vapors may form explosive mixtures with air. By heating and fire, corrosive vapors/gases may be formed. Carbon oxides. Silicon oxides. Formaldehyde.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

Fire fighting equipment/instructions

In the event of fire, cool tanks with water spray. Move containers from fire area if you can do it without risk. Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Combustible liquid.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Ventilate closed spaces before entering. Avoid inhalation of vapors and contact with skin and eyes. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Wear appropriate protective equipment and clothing during clean-up. See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. After removal flush contaminated area thoroughly with water.

Never return spills to original containers for re-use. This material and its container must be disposed of as hazardous waste.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage**Precautions for safe handling**

Use only with adequate ventilation. Avoid inhalation of vapors and contact with skin and eyes. Wear approved safety goggles. Wear protective gloves and appropriate clothing to prevent skin contact. Observe good industrial hygiene practices. When cured: Avoid generation and spreading of dust.

Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

8. Exposure controls/personal protection**Occupational exposure limits****U.S. - OSHA**

Components	Type	Value
Carbon fiber (CAS 7440-44-0)	TWA	15 mppcf

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm	
Graphite (CAS 7782-42-5)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
m-Cresol (CAS 108-39-4)	PEL	22 mg/m3 5 ppm	
Phenol (CAS 108-95-2)	PEL	19 mg/m3 5 ppm	

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon fiber (CAS 7440-44-0)	TWA	5 mg/m3	Respirable fraction.
Graphite (CAS 7782-42-5)	TWA	15 mg/m3	Total dust.
Quartz (CAS 14808-60-7)	TWA	15 mppcf	
		0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum hydroxide (CAS 21645-51-2)	TWA	1 mg/m3	Respirable fraction.
Carbon fiber (CAS 7440-44-0)	TWA	2 mg/m3	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Ethanol (CAS 64-17-5)	STEL	1000 ppm	
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction.
m-Cresol (CAS 108-39-4)	TWA	20 mg/m ³	Inhalable fraction and vapor.
Phenol (CAS 108-95-2)	TWA	5 ppm	
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Carbon fiber (CAS 7440-44-0)	TWA	2.5 mg/m ³	Respirable.
Ethanol (CAS 64-17-5)	TWA	1900 mg/m ³ 1000 ppm	
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m ³	Respirable.
m-Cresol (CAS 108-39-4)	TWA	10 mg/m ³ 2.3 ppm	
Phenol (CAS 108-95-2)	Ceiling	60 mg/m ³ 15.6 ppm	
	TWA	19 mg/m ³ 5 ppm	
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.
Refractories, Fibers, Aluminosilicate (CAS 142844-00-6)	TWA	3 fibers/cm ³	Fiber.
		3 fibers/cm ³	Dust.
		5 mg/m ³	fibers, total dust
		5 mg/m ³	Fiber, total

Biological limit values No biological exposure limits noted for the ingredient(s).

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Phenol (CAS 108-95-2)	250 mg/g	Phenol with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines No exposure standards allocated.

US - California OELs: Skin designation

m-Cresol (CAS 108-39-4) Can be absorbed through the skin.
Phenol (CAS 108-95-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

m-Cresol (CAS 108-39-4) Skin designation applies.
Phenol (CAS 108-95-2) Skin designation applies.

US - Tennessee OELs: Skin designation

m-Cresol (CAS 108-39-4) Can be absorbed through the skin.
Phenol (CAS 108-95-2) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

m-Cresol (CAS 108-39-4) Can be absorbed through the skin.
Phenol (CAS 108-95-2) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Phenol (CAS 108-95-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

m-Cresol (CAS 108-39-4) Can be absorbed through the skin.
Phenol (CAS 108-95-2) Can be absorbed through the skin.

Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors. An eye wash and safety shower must be available in the immediate work area.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection	
Hand protection	Wear protective gloves. Butyl rubber gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.
Other	Wear appropriate clothing to prevent possibility of skin contact.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Black pliable semi-solid with phenolic odor.
Physical state	Liquid.
Form	Pliable semi-solid.
Color	Black.
Odor	Phenolic.
Odor threshold	0.003 - 5 ppm (m-Cresol)
pH	Not available.
Melting point/freezing point	Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	160.0 °F (71.1 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Slightly.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	> 1200 °F (> 648.89 °C) When cured
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Flammability	Combustible solid.
Flash point class	Combustible IIIA

10. Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Flames and sparks. Avoid contact with incompatible materials.

Incompatible materials	Strong oxidizers, strong acids, and strong bases. Strong reducing agents.
Hazardous decomposition products	Oxides of aluminum. Carbon oxides. Silicon oxides. Formaldehyde. Unidentified organic compounds.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause severe respiratory tract irritation. May cause burns in mucous membranes, throat, esophagus and stomach. When cured: Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material.
Skin contact	May cause skin burns. May cause an allergic skin reaction. Components of the product may be absorbed into the body through the skin.
Eye contact	May cause eye burns. Risk of serious damage to eyes.
Ingestion	May cause digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Unconsciousness. Coughing. Shortness of breath. Irritation of nose and throat. Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness and tearing. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure.

Information on toxicological effects

Acute toxicity May cause severe respiratory tract irritation. May cause damage to the liver and kidneys. May cause skin, eye and digestive tract burns.

Components	Species	Test Results
Aluminum hydroxide (CAS 21645-51-2)		
Acute		
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg
Carbon fiber (CAS 7440-44-0)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 2000 mg/m3, 4 hours
Ethanol (CAS 64-17-5)		
Acute		
<i>Inhalation</i>		
LC50	Rat	30000 mg/m3
m-Cresol (CAS 108-39-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	620 mg/kg
<i>Oral</i>		
LD50	Rat	242 mg/kg
Phenol (CAS 108-95-2)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	630 mg/kg
<i>Oral</i>		
LD50	Rat	340 mg/kg
Skin corrosion/irritation	May cause skin burns.	
Serious eye damage/eye irritation	May cause eye burns. Risk of serious damage to eyes.	
Respiratory or skin sensitization		
Respiratory sensitization	Not classified.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	Contains a substance which may have a mutagenic effect.	
Carcinogenicity	Not classified.	

IARC Monographs. Overall Evaluation of Carcinogenicity

Phenol (CAS 108-95-2)	3 Not classifiable as to carcinogenicity to humans.
Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.
Refractories, Fibers, Aluminosilicate (CAS 142844-00-6)	2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Quartz (CAS 14808-60-7)	Known To Be Human Carcinogen.
-------------------------	-------------------------------

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	Contains no ingredient listed as toxic to reproduction.
Specific target organ toxicity - single exposure	Not available.
Specific target organ toxicity - repeated exposure	May cause damage to organs (kidney, liver) through prolonged or repeated exposure.
Aspiration hazard	Not classified.
Chronic effects	Danger of serious damage to health by prolonged exposure. May cause damage to the liver and kidneys. When cured: Phenolic resin releases formaldehyde and formaldehyde has carcinogenic potential and is a known skin and respiratory sensitizer.
Further information	Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure.

12. Ecological information

Ecotoxicity	The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Components	Species	Test Results	
Hexamethylenetetramine (CAS 100-97-0)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	29868 - 43390 mg/l, 48 hours
Fish	LC50	Bleak (Alburnus alburnus)	> 10000 mg/l, 96 hours
m-Cresol (CAS 108-39-4)			
Aquatic			
Crustacea	EC50	Scud (Gammarus fasciatus)	7 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.9 mg/l, 96 hours
Phenol (CAS 108-95-2)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia obtusa)	4.7 - 6.4 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	7.5 - 14 mg/l, 96 hours

Persistence and degradability	The product contains inorganic compounds which are not biodegradable.
--------------------------------------	---

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethanol (CAS 64-17-5)	-0.31
Phenol (CAS 108-95-2)	1.46
m-Cresol (CAS 108-39-4)	1.96

Mobility in soil	Expected to be slightly to moderately mobile in soil.
-------------------------	---

Mobility in general	The product is slightly soluble in water. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.
----------------------------	--

Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential. The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
------------------------------	---

13. Disposal considerations

Disposal instructions	Dispose of this material and its container to hazardous or special waste collection point. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
------------------------------	---

Hazardous waste code D026: Waste Cresol
Waste from residues / unused products Dispose of in accordance with local regulations.
Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

DOT BULK

BULK

UN number UN1760
UN proper shipping name Corrosive liquids, n.o.s.
Transport hazard class(es)
 Class 8
 Label(s) 8
Packing group II
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Special provisions B2, IB2, T11, TP2, TP27
Packaging exceptions 154
Packaging non bulk 202
Packaging bulk 242

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Refractories, Fibers, Aluminosilicate (CAS 142844-00-6) 0.1 % One-Time Export Notification only.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethanol (CAS 64-17-5)	LISTED
m-Cresol (CAS 108-39-4)	LISTED
Phenol (CAS 108-95-2)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Phenol	108-95-2	1000		500	10000

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
m-Cresol	108-39-4	1-5
Phenol	108-95-2	1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

m-Cresol (CAS 108-39-4)

Phenol (CAS 108-95-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Ethanol (CAS 64-17-5)

Graphite (CAS 7782-42-5)

m-Cresol (CAS 108-39-4)

Phenol (CAS 108-95-2)

Quartz (CAS 14808-60-7)

Refractories, Fibers, Aluminosilicate (CAS 142844-00-6)

US. New Jersey Worker and Community Right-to-Know Act

Carbon fiber (CAS 7440-44-0)

Ethanol (CAS 64-17-5)

Graphite (CAS 7782-42-5)

Hexamethylenetetramine (CAS 100-97-0)

m-Cresol (CAS 108-39-4)

Phenol (CAS 108-95-2)

Quartz (CAS 14808-60-7)

Refractories, Fibers, Aluminosilicate (CAS 142844-00-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethanol (CAS 64-17-5)

Graphite (CAS 7782-42-5)

m-Cresol (CAS 108-39-4)

Phenol (CAS 108-95-2)

Quartz (CAS 14808-60-7)

Refractories, Fibers, Aluminosilicate (CAS 142844-00-6)

US. Rhode Island RTK

m-Cresol (CAS 108-39-4)

Phenol (CAS 108-95-2)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Quartz (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 15-April-2015
Revision date -
Version # 01
Further information HMIS® is a registered trade and service mark of the NPCA.
I - Safety Glasses, Gloves, Dust, Vapor Respirator
HMIS® ratings Health: 3*
Flammability: 2
Physical hazard: 0
Personal protection: I

NFPA ratings



List of abbreviations

References

ACGIH
EPA: Acquire database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices
ESIS (European chemical Substances Information System)
IARC: International Agency for Research on Cancer.

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.