

TEAM® Industrial Services
SAFETY DATA SHEET

1. Identification

Product identifier S-180 SF PRP SEALANT

Other means of identification

Product code 900-0039

Recommended use Industrial Leak Sealant.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name Team Industrial Services, Inc.
Address 200 Hermann Drive, Alvin, Texas 77511
Telephone Not available.
E-mail Not available.

Emergency phone number CHEMTREC - 24 HOURS: 800-424-9300 (USA)
International: +1 703-527-3887 (Collect)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 4

Health hazards Reproductive toxicity Category 2
Specific target organ toxicity, repeated exposure Category 2 (Central nervous system)

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3
Hazardous to the aquatic environment, long-term hazard Category 3

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Combustible liquid. Suspected of damaging the unborn child. May cause damage to organs (Central nervous system) through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe the mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response In case of fire: Use appropriate media for extinction. If exposed or concerned: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Aluminum oxide	1344-28-1	25-50
Polymer	25034-71-3	25-50
Graphite	7782-42-5	10-25
Carbon fiber	7440-44-0	<5
Dicumyl peroxide	80-43-3	<5
Toluene	108-88-3	<5

Composition comments All concentrations are in percent by weight.

4. First-aid measures

Inhalation	Move to fresh air. Get medical attention if any discomfort occurs.
Skin contact	Remove contaminated clothing and shoes. Flush thoroughly with water for at least 15 minutes. If irritation occurs, get medical assistance.
Eye contact	Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.
Ingestion	Rinse mouth thoroughly with water and give large amounts of milk or water, if person is conscious. Never give anything by mouth to a victim who is unconscious or is having convulsions. Only induce vomiting at the instruction of medical personnel. If vomiting occurs, keep head low so that stomach content does not get into the lungs. Get medical attention immediately.
Most important symptoms/effects, acute and delayed	Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness and tearing.
Indication of immediate medical attention and special treatment needed	Be aware that symptoms of chemical pneumonia (shortness of breath) may occur several hours after exposure.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	No restrictions known.
Specific hazards arising from the chemical	Solvent vapors may form explosive mixtures with air. By heating and fire, corrosive vapors/gases may be formed. Carbon oxides. Silicon oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Fire fighting equipment/instructions	In the event of fire, cool tanks with water spray. Move containers from fire area if you can do it without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Ventilate closed spaces before entering. Avoid inhalation of vapors and contact with skin and eyes. Wear appropriate protective equipment and clothing during clean-up. See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. After removal flush contaminated area thoroughly with water. This material and its container must be disposed of as hazardous waste.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

Pregnant or breastfeeding women must not handle this product. Avoid inhalation of vapors and contact with skin and eyes. The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. Ground container and transfer equipment to eliminate static electric sparks. Use non-sparking tools and explosion-proof equipment. Use only with adequate ventilation. Wear approved safety goggles. Wear protective gloves and appropriate clothing to prevent skin contact. Avoid generation and spreading of dust. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep away from food, drink and animal feedings.

8. Exposure controls/personal protection

Occupational exposure limits

U.S. - OSHA

Components	Type	Value
Carbon fiber (CAS 7440-44-0)	TWA	15 mppcf

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum oxide (CAS 1344-28-1)	PEL	5 mg/m ³	Respirable fraction.
Graphite (CAS 7782-42-5)	PEL	15 mg/m ³	Total dust.
		5 mg/m ³	Respirable fraction.
		15 mg/m ³	Total dust.

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Carbon fiber (CAS 7440-44-0)	TWA	5 mg/m ³	Respirable fraction.
Graphite (CAS 7782-42-5)	TWA	15 mg/m ³	Total dust.
		15 mppcf	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum oxide (CAS 1344-28-1)	TWA	1 mg/m ³	Respirable fraction.
Carbon fiber (CAS 7440-44-0)	TWA	2 mg/m ³	Respirable fraction.
Graphite (CAS 7782-42-5)	TWA	2 mg/m ³	Respirable fraction.
Toluene (CAS 108-88-3)	TWA	20 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Carbon fiber (CAS 7440-44-0)	TWA	2.5 mg/m ³	Respirable.
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m ³	Respirable.
Toluene (CAS 108-88-3)	STEL	560 mg/m ³	
		150 ppm	
		375 mg/m ³	
	TWA	100 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of vapors.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles.

Skin protection

Hand protection

Wear protective gloves. Polyvinyl alcohol gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing to prevent any possibility of skin contact.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

Thermal hazards

When material is heated, wear gloves to protect against thermal burns.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and working clothes should be kept separately.

9. Physical and chemical properties

Appearance

Black pliable semi-solid with solvent odor.

Physical state

Liquid.

Form

Pliable semi-solid.

Color

Black.

Odor

Solvent.

Odor threshold

Not available.

pH

Not available.

Melting point/freezing point

Not available.

Initial boiling point and boiling range

230 °F (110 °C)

Flash point

198.0 °F (92.2 °C) Closed Cup

Evaporation rate

1 (Butyl acetate=1)

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

6 mm Hg @ 68 F

Vapor density

Not available.

Relative density	0.9
Solubility(ies)	
Solubility (water)	Negligible.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Flash point class	Combustible IIIA

10. Stability and reactivity

Reactivity	The product is non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Flames and sparks.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	High concentrations: Vapors may cause drowsiness and dizziness.
Skin contact	May cause skin irritation. Prolonged or repeated contact may dry skin and cause dermatitis. Components of the product may be absorbed into the body through the skin.
Eye contact	May cause eye irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Coughing. Irritation of eyes and mucous membranes. Symptoms include itching, burning, redness and tearing.

Information on toxicological effects

Acute toxicity May cause discomfort if swallowed. May cause central nervous system effects.

Components	Species	Test Results
Carbon fiber (CAS 7440-44-0)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 2000 mg/m3, 4 hours
Dicumyl peroxide (CAS 80-43-3)		
Acute		
<i>Oral</i>		
LD50	Rat	4100 mg/kg
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	14.1 ml/kg
<i>Inhalation</i>		
LC50	Rat	49000 mg/m ³ , 4 Hours
<i>Oral</i>		
LD50	Rat	636 mg/kg
Skin corrosion/irritation	May cause skin irritation.	
Serious eye damage/eye irritation	May cause eye irritation.	

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization Not a skin sensitizer.

Germ cell mutagenicity Not available.

Carcinogenicity Not classified.

IARC Monographs. Overall Evaluation of Carcinogenicity

Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity May adversely affect the developing fetus based on animal data. Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure Not available.

Specific target organ toxicity - repeated exposure May cause damage to organs (Central nervous system) through prolonged or repeated exposure.

Aspiration hazard Not classified.

Chronic effects Danger of serious damage to health by prolonged exposure. Organic solvents may be absorbed into the body by inhalation and ingestion and cause permanent damage to the nervous system, including the brain.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
Toluene (CAS 108-88-3)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Pink salmon (<i>Oncorhynchus gorbuscha</i>) 6.86 - 8.48 mg/l, 96 hours

Persistence and degradability The product contains inorganic compounds which are not biodegradable.

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient n-octanol / water (log Kow)

Dicumyl peroxide (CAS 80-43-3)	5.5
Toluene (CAS 108-88-3)	2.73

Mobility in soil No data available.

Mobility in general The product contains substances which are insoluble in water and which sediment in water systems. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Dispose of this material and its container to hazardous or special waste collection point. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Hazardous waste code Not regulated.

Waste from residues / unused products Dispose of in accordance with local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Toluene (CAS 108-88-3) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminum oxide	1344-28-1	25-50
Toluene	108-88-3	<5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

US state regulations

US. Massachusetts RTK - Substance List

Aluminum oxide (CAS 1344-28-1)
Graphite (CAS 7782-42-5)
Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Aluminum oxide (CAS 1344-28-1)
Carbon fiber (CAS 7440-44-0)
Graphite (CAS 7782-42-5)
Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum oxide (CAS 1344-28-1)
Graphite (CAS 7782-42-5)
Toluene (CAS 108-88-3)

US. Rhode Island RTK

Aluminum oxide (CAS 1344-28-1)

Toluene (CAS 108-88-3)

US. California Proposition 65**US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance**

Toluene (CAS 108-88-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 15-April-2015**Revision date** -**Version #** 01**Further information** HMIS® is a registered trade and service mark of the NPCA.**HMIS® ratings**
Health: 1*
Flammability: 2
Physical hazard: 0**List of abbreviations****References**ACGIH
EPA: Acquire database
NLM: Hazardous Substances Data Base
US. IARC Monographs on Occupational Exposures to Chemical Agents
HSDB® - Hazardous Substances Data Bank
IARC Monographs. Overall Evaluation of Carcinogenicity
National Toxicology Program (NTP) Report on Carcinogens
ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available.